



WAT Motor
Sanayi ve Ticaret A.Ş.



Three Phase Squirrel Cage Induction Motor

Motor Type: Q1H80M4-8B

Electrical Data

RATED VALUES							STARTING VALUES			BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos ϕ	CURRENT		TORQUE	TORQUE				IEC 60034-30-1
V	kW	Hz	rpm	A	Nm	4/4	I_A / I_N	YY	M_A / M_N	Mk/ Mn	4/4	3/4	2/4	IE
400	0,18	50	720	1,0	2,4	0,50	2,9		1,5	2,8				
400	0,33	50	1438	0,8	2,2	0,83		5,4	1,8	1,4				

Mechanical Data


Bearing DE	6204-ZZ	Color	Optional
Bearing NDE	6204-ZZ	Motor protection	Optional
Lubricants	Shell Gadus S2 V100Q2	Method of cooling	IC 411
Condensation drain hole	No	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Aluminium
Vibration class	A	Terminal plate thread	M4
Insulation class	F	Cable gland	1xM20
Duty type	S1	Clamping range	10-14 mm
Direction of rotation	Clockwise	Mounting type	IM 1001 (B3)
Housing material	Aluminum		
Type of balancing	Half Key		

Enviromental Data

Others

Ambient temperature	-20 / + 40 °C	Type of protection	IP55
Altitude above sea level	1000 m	Sound pressure level 50/60Hz	64
		Moment of inertia (kgm ²)	0,00196
		Standard	IEC 60034-1
		Weight (kg)	

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
158	268	100	125	80	216	10	50	19	40	21,5	6				