



WAT Motor  
Sanayi ve Ticaret A.Ş.



## Three Phase Squirrel Cage Induction Motor

Motor Type: Q2EPB71M2A

### Electrical Data

| RATED VALUES |       |    |       |           |        |            | STARTING VALUES |   |             | BREAKDOWN    | EFFICIENCY |      |      | EFFICIENCY CLASS |
|--------------|-------|----|-------|-----------|--------|------------|-----------------|---|-------------|--------------|------------|------|------|------------------|
| VOLTAGE      | POWER |    | SPEED | CURRENT   | TORQUE | Cos $\phi$ | CURRENT         |   | TORQUE      | TORQUE       |            |      |      | IEC 60034-30-1   |
| V            | kW    | Hz | rpm   | A         | Nm     | 4/4        | $I_A / I_N$     | D | $M_A / M_N$ | Mk/ Mn<br>Nm | 4/4        | 3/4  | 2/4  | IE               |
| 230/400      | 0,37  | 50 | 2784  | 1,65/0,95 | 1,3    | 0,86       | 4,90            |   | 2,70        | 2,90         | 69,5       | 67,8 | 66,7 | IE2              |
| 265/460      | 0,37  | 60 | 3425  | 1,44/0,83 | 1,0    | 0,76       | 4,68            |   | 3,00        | 3,84         | 72,2       | 72,8 | 71,7 | IE2              |
|              |       |    |       |           |        |            |                 |   |             |              |            |      |      |                  |
|              |       |    |       |           |        |            |                 |   |             |              |            |      |      |                  |

### Mechanical Data


|                            |                       |                          |                 |
|----------------------------|-----------------------|--------------------------|-----------------|
| Bearing DE                 | 6202-ZZ               | Color                    | Optional        |
| Bearing NDE                | 6202-ZZ               | Motor protection         | Optional        |
| Lubricants                 | Shell Gadus S2 V100Q2 | Method of cooling        | IC 411          |
| Condensation drain hole    | No                    | Terminal box position    | Top             |
| External earthing terminal | Yes                   | Material of terminal box | Aluminium       |
| Vibration class            | A                     | Terminal plate thread    | M4              |
| Insulation class           | F                     | Cable gland              | 1xM20           |
| Duty type                  | S1                    | Clamping range           | 10-14 mm        |
| Direction of rotation      | Clockwise             | Mounting type            | IM 2101 (B34-B) |
| Housing material           | Aluminum              |                          |                 |
| Type of balancing          | Half Key              |                          |                 |

### Enviromental Data

### Others

|                          |               |                                       |             |
|--------------------------|---------------|---------------------------------------|-------------|
| Ambient temperature      | -20 / + 40 °C | Type of protection                    | IP56        |
| Altitude above sea level | 1000 m        | Sound pressure level 50/60Hz          | dBA 58      |
|                          |               | Moment of inertia (kgm <sup>2</sup> ) | 0,00032     |
|                          |               | Standard                              | IEC 60034-1 |
|                          |               | Weight (kg)                           | 6,0         |

### Dimensions



| Main Dimensions |     | Foot Mounted Motors |     |    |     |   |    | Shaft |    |    |   | Flange Mounted Motors |    |     |    |
|-----------------|-----|---------------------|-----|----|-----|---|----|-------|----|----|---|-----------------------|----|-----|----|
| AC              | L   | B                   | A   | H  | HD  | K | C  | D     | E  | GA | F | P                     | N  | M   | S  |
| 138             | 253 | 90                  | 112 | 71 | 178 | 7 | 45 | 14    | 30 | 16 | 5 | 140                   | 95 | 115 | M8 |