




WAT Motor
Sanayi ve Ticaret A.Ş.

Three Phase Squirrel Cage Induction Motor

Motor type Q3HG112M4D40-KG



Electrical Data

RATED VALUES							STARTING VALUES			BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS	
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos Φ	CURRENT		TORQUE	TORQUE	%			IEC 60034-30-1	
V	kW	Hz	rpm	A	Nm	4/4	I _A / I _N Y D		M _A / M _N Y D	M _k / M _n Nm	4/4	3/4	2/4	IE	
400/690	4	50	1459	8,5/4,9	26,10	0,77	-	9,7	-	4	4,7	88,6	87,9	85,7	IE3
460/795	4,6	60	1755	8,2/4,7	25,00	0,79	-	9,4	-	3,8	4,5	-	-	-	

Mechanical Data


Bearing DE	6306-ZZ C3	Color	RAL 3009
Bearing NDE	6306-ZZ C3	Motor protection	-
Lubricants	Standart	Method of cooling	IC411 (TEFC)
Condensation drain hole	Optional	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Cast Iron
Vibration class	A	Terminal plate thread	M5
Insulation Class	F	Cable gland	2xM25G
Duty type	S1	Clamping range	13-18 mm
Direction of rotation	CW/CCW	Mounting type	IM 1001 (B3)
Housing material	Cast Iron		
Type of balancing	H		

Environmental Data

Others

Ambient Temperature	-20 / + 40 °C	Type of protection	IP 56
Altitude above sea level	1000 m	Sound Pressure Level 50Hz dBA	54
		Moment of Inertia (kg.mm ²)	0,0138288
		Standard	IEC 60034-1

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
222	459	140	190	112	290	12	70	28	60	31	8	-	-	-	-