




WAT Motor
Sanayi ve Ticaret A.Ş.

Three Phase Squirrel Cage Induction Motor

Motor type Q3HG200L2C40-KI



Electrical Data

RATED VALUES							STARTING VALUES				BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS			
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos φ	CURRENT		TORQUE		TORQUE	%			IEC 60034-30-1			
V	kW	Hz	rpm	A	Nm	4/4	I _A / I _N	Y	D	M _A / M _N	Y	D	Mk/ Mn	Nm	4/4	3/4	2/4	IE
400/690	30	50	2964	51,2/29,5	97,60	0,91	-	10,4	-	2,7			4,1		93,3	92,8	91,6	IE3
460/795	34,5	60	3564	50,6/29,2	92,60	0,92	-	10,1	-	2,6			4,0		-	-	-	

Mechanical Data


Bearing DE	6312-ZZ C3	Color	RAL 3009
Bearing NDE	6310-ZZ C3	Motor protection	PTC
Lubricants	Standart	Method of cooling	IC411 (TEFC)
Condensation drain hole	Optional	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Cast Iron
Vibration class	A	Terminal plate thread	M8
Insulation Class	F	Cable gland	2xM50G+1xM16G
Duty type	S1	Clamping range	30-38 mm
Direction of rotation	CW/CCW	Mounting type	IM 1001 (B3)
Housing material	Cast Iron		
Type of balancing	H		

Environmental Data

Others

Ambient Temperature	-20 / + 40 °C	Type of protection	IP 56
Altitude above sea level	1000 m	Sound Pressure Level 50Hz dBA	78
		Moment of Inertia (kg.mm ²)	0,102772
		Standard	IEC 60034-1

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
356	763	305	318	200	458	18,5	133	55	110	59	16	-	-	-	-