




WAT Motor
Sanayi ve Ticaret A.Ş.

Three Phase Squirrel Cage Induction Motor

Motor type Q3HGPA132M6B40-KG



Electrical Data

RATED VALUES							STARTING VALUES				BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos ϕ	CURRENT		TORQUE		TORQUE	%			IEC 60034-30-1
V	kW	Hz	rpm	A	Nm	4/4	I _A / I _N Y D		M _A / M _N Y D		M _k / M _n Nm	4/4	3/4	2/4	IE
400/690	5,5	50	977	12,6/7,3	53,70	0,71	-	5,7	-	1,7	2,8	88,0	88,1	86,9	IE3
460/795	6,3	60	1179	11,2/6,5	44,50	0,69	-	5,5	-	1,6	2,7	-	-	-	

Mechanical Data


Bearing DE	6308-ZZ C3	Color	RAL 3009
Bearing NDE	6308-ZZ C3	Motor protection	-
Lubricants	Standart	Method of cooling	IC411 (TEFC)
Condensation drain hole	Optional	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Cast Iron
Vibration class	A	Terminal plate thread	M6
Insulation Class	F	Cable gland	2xM32G
Duty type	S1	Clamping range	18-25 mm
Direction of rotation	CW/CCW	Mounting type	IM 2001 (B35)
Housing material	Cast Iron		
Type of balancing	H		

Environmental Data

Others

Ambient Temperature	-20 / + 40 °C	Type of protection	IP 56
Altitude above sea level	1000 m	Sound Pressure Level 50Hz dBA	60
		Moment of Inertia (kg.mm ²)	0,0594
		Standard	IEC 60034-1

Dimensions



Main Dimensions		Foot Mounted Motors							Shaft		Flange Mounted Motors				
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
273	533	178	216	132	337	14,5	89	38	80	41	10	300	230	265	14,5