



WAT Motor
Sanayi ve Ticaret A.Ş.



Three Phase Squirrel Cage Induction Motor

Motor Type: Q3HPA180M2A

Electrical Data

RATED VALUES							STARTING VALUES			BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos Φ	CURRENT		TORQUE	TORQUE				IEC 60034-30-1
V	kW	Hz	rpm	A	Nm	4/4	I_A / I_N	M_A / M_N	M_k / M_n	Nm	4/4	3/4	2/4	IE
400/690	22	50	2960	37,0/21,4	71,0	0,92		11,2	3,2	4,2	92,7	92,5	91,3	IE3
460/795	22	60	3570	33,4/19,3	58,8	0,89		12,44	3,55	5,55	91,7	91,5	90,1	IE3

Mechanical Data


Bearing DE	6310-ZZ	Color	Optional
Bearing NDE	6310-ZZ	Motor protection	Optional
Lubricants	Shell Gadus S5 V220-2	Method of cooling	IC 411
Condensation drain hole	No	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Aluminium
Vibration class	A	Terminal plate thread	M8
Insulation class	F	Cable gland	1xM40
Duty type	S1	Clamping range	22-32 mm
Direction of rotation	Clockwise	Mounting type	IM 2001 (B35)
Housing material	Aluminium		
Type of balancing	Half Key		

Enviromental Data

Others

Ambient temperature	-20 / + 40 °C	Type of protection	IP56
Altitude above sea level	1000 m	Sound pressure level 50/60Hz	dBA 76
		Moment of inertia (kgm^2)	0,09460
		Standard	IEC 60034-1
		Weight (kg)	135,0

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
349	696	241-279	279	180	437	14,5	121	48	110	51,5	14	350	250	300	18,5

B34b