



WAT Motor
Sanayi ve Ticaret A.Ş.



Three Phase Squirrel Cage Induction Motor

Motor Type: Q4H180L6C

Electrical Data

RATED VALUES							STARTING VALUES				BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos Φ	CURRENT		TORQUE		TORQUE				IEC 60034-30-1
I _A / I _N	M _A / M _N	Mk/ Mn													
Y	D	Y	D	Nm	4/4	3/4	2/4	IE							
400/690	15	50	984	32,1/18,5	145,6	0,73	5,3		1,7		2,3	92,9	92,6	91,9	IE4
460/795	15	60	1186	28,5/16,4	120,8	0,71	5,1		1,9		3,0	93,0	92,4	90,0	IE4

Mechanical Data


Bearing DE	6310-ZZ	Color	Optional
Bearing NDE	6310-ZZ	Motor protection	Optional
Lubricants	Shell Gadus S5 V220-2	Method of cooling	IC 411
Condensation drain hole	No	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Aluminium
Vibration class	A	Terminal plate thread	M8
Insulation class	F	Cable gland	1xM40
Duty type	S1	Clamping range	22-32 mm
Direction of rotation	Clockwise	Mounting type	IM 1001 (B3)
Housing material	Aluminum		
Type of balancing	Half Key		

Enviromental Data

Others

Ambient temperature	-20 / + 40 °C	Type of protection	IP56
Altitude above sea level	1000 m	Sound pressure level 50/60Hz	76 dBA
		Moment of inertia (kgm ²)	0,23683
		Standard	IEC 60034-1
		Weight (kg)	185,0

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
349	750	241-279	279	180	437	14,5	121	48	110	51,5	14				