



WAT Motor
Sanayi ve Ticaret A.Ş.



Smoke Extraction Motor F400 2 Hour EN 12101-3

Motor Type: S3HG200L2C40-KG

Electrical Data

RATED VALUES							STARTING VALUES			BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos Φ	CURRENT		TORQUE	TORQUE				IEC 60034-30-1
V	kW	Hz	rpm	A	Nm	4/4	I_A / I_N	D	M_A / M_N	Mk/ Mn Nm	4/4	3/4	2/4	IE
400/690	30	50	2973	51,2/29,5	96,4	0,91		10,20	3,00	4,70	IE3-93,3	92,8	91,8	IE3
460/795	30	60	3574	46,0/26,5	80,2	0,90		9,69	2,85	4,47	IE3-92,4	91,9	90,7	IE3

Mechanical Data


Bearing DE	6312 ZZ C4 DUPONT260C ORS	Color	Optional
Bearing NDE	6310 ZZ C4 DUPONT260C ORS	Motor protection	Optional
Lubricants	Dupont GPL 226 Krytox (260 C°)	Method of cooling	IC 418
Condensation drain hole	No	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Cast Iron
Vibration class	A	Cable gland	M40x1.5
Insulation class	H	Clamping range	22-32
Duty type	S1	Mounting type	IM 1001 (B3)
Direction of rotation	Clockwise		
Housing material	Cast Iron		
Type of balancing	Half Key		

Enviromental Data

Others

Ambient temperature	-20 / + 40 °C	Type of protection	IP56
Altitude above sea level	1000 m	Sound pressure level 50/60Hz	dBA 78
		Moment of inertia (kgm ²)	0,10277
		Standard	IEC 60034-1
		Weight (kg)	206,4
		Resistance to fire	400 C° 2 Hour F400 EN 12101-3

Dimensions



Main Dimensions			Foot Mounted Motors					Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
355	680	305	318	200	484	18,5	135	55	110	59	16				