



WAT Motor
Sanayi ve Ticaret A.Ş.



Smoke Extraction Motor F400 2 Hour EN 12101-3

Motor Type: S3HG90L4C40-KG

Electrical Data

RATED VALUES							STARTING VALUES				BREAKDOWN	EFFICIENCY			EFFICIENCY CLASS
VOLTAGE	POWER		SPEED	CURRENT	TORQUE	Cos Φ	CURRENT		TORQUE		TORQUE				IEC 60034-30-1
V	kW	Hz	rpm	A	Nm	4/4	I_A / I_N	D	M_A / M_N	D	Mk/ Mn Nm	4/4	3/4	2/4	IE
230/400	1,1	50	1443	4,5/2,6	7,3	0,77	7,40		3,60		4,10	IE3-84,1	81	77,3	IE3
265/460	1,1	60	1720	4,3/2,5	6,1	0,82	7,03		3,42		3,90	IE3-86,5	85,6	82,9	IE3

Mechanical Data


Bearing DE	6305 ZZ C4 DUPONT260C ORS	Color	Optional
Bearing NDE	6205 ZZ C4 DUPONT260C ORS	Motor protection	Optional
Lubricants	Dupont GPL 226 Krytox (260 C°)	Method of cooling	IC 418
Condensation drain hole	No	Terminal box position	Top
External earthing terminal	Yes	Material of terminal box	Cast Iron
Vibration class	A	Cable gland	M25x1.5
Insulation class	H	Clamping range	13-18
Duty type	S1	Mounting type	IM 1001 (B3)
Direction of rotation	Clockwise		
Housing material	Cast Iron		
Type of balancing	Half Key		

Enviromental Data

Others

Ambient temperature	-20 / + 40 °C	Type of protection	IP56
Altitude above sea level	1000 m	Sound pressure level 50/60Hz	dBA 53
		Moment of inertia (kgm ²)	0,00464
		Standard	IEC 60034-1
		Weight (kg)	28,6
		Resistance to fire	400 C° 2 Hour F400 EN 12101-3

Dimensions



Main Dimensions		Foot Mounted Motors						Shaft				Flange Mounted Motors			
AC	L	B	A	H	HD	K	C	D	E	GA	F	P	N	M	S
185	325	125	140	90	242	10	56	24	50	27	8				